





# Female and male cable coupler MC4

Female and male cable coupler as individual part (including insulating part)

PV-KBT4...



PV-KST4...



Order No.	Type	Female cable coupler	Male cable coupler	Ø range of cable gland	Conductor cross section			Approvals							
					A (mm)	mm <sup>2</sup>	AWG	b (mm)	TÜV	RU	SF	CBC			
32.0010P0001-UR	PV-KBT4/2,5I-UR	x		3 – 6	1.5; 2.5	14	3	x	x	x	x				
32.0011P0001-UR	PV-KST4/2,5I-UR		x	3 – 6	1.5; 2.5	14	3								
32.0012P0001-UR	PV-KBT4/2,5II-UR	x		5.5 – 9	1.5; 2.5	14	3								
32.0013P0001-UR	PV-KST4/2,5II-UR		x	5.5 – 9	1.5; 2.5	14	3								
32.0014P0001-UR	PV-KBT4/6I-UR	x		3 – 6	4; 6	12; 10	5								
32.0015P0001-UR	PV-KST4/6I-UR		x	3 – 6	4; 6	12; 10	5								
32.0016P0001-UR	PV-KBT4/6II-UR	x		5.5 – 9	4; 6	12; 10	5								
32.0017P0001-UR	PV-KST4/6II-UR		x	5.5 – 9	4; 6	12; 10	5								
32.0080-UR	PV-KBT4/8II-UR	x		6.5 – 8.9	–	8	–					x	x		
32.0081-UR	PV-KST4/8II-UR		x	6.5 – 8.9	–	8	–								
32.0034P0001	PV-KBT4/10II	x		5.5 – 9	10	–	7.2	x		x	x				
32.0035P0001	PV-KST4/10II		x	5.5 – 9	10	–	7.2								



Sealing caps page 56

Assembly tools page 61



Assembly Instructions MA231

[www.staubli.com/electrical](http://www.staubli.com/electrical)

- Snap-in lock
- Locking by safety lock clip PV-SSH4 in accordance with NEC 2011, can be released only with tool
- Proven MULTILAM technology with high long-term stability, which ensures consistently low performance loss throughout the entire service life of the plug connector
- Tried and tested plug connectors, 14 years of experience in the field
- Available for assembly with cross-sections of 10 mm<sup>2</sup>
- Also available as ready made leads, see page 66
- Leads made to customer's specifications, see page 68

Technical data	
Connector system	Ø 4 mm
Rated voltage	1000 V DC (IEC 62852) 1500 V DC (2Pfg2330) <sup>1)</sup> 600 V DC / 1000 V DC / 1500 V DC (UL) <sup>2)</sup>
Rated current IEC (85 °C)	17 A (1.5 mm <sup>2</sup> ) 22.5 A (2.5 mm <sup>2</sup> ; 14 AWG) 39 A (4 mm <sup>2</sup> , 6 mm <sup>2</sup> ; 12 AWG, 10 AWG) 45 A (10 mm <sup>2</sup> )
Rated impulse voltage	12 kV (1000 V DC (IEC)) 16 kV (1500 V DC (IEC))
Ambient temperature range	-40 °C...+85 °C (IEC)
Upper limiting temperature	105 °C (IEC)
Degree of protection, mated unmated	IP65, IP68 (1 h/1 m) IP2X
Overvoltage category/Pollution degree	CATIII/3
Contact resistance of plug connectors	≤ 0.25 mΩ
Safety class	1000 V DC: II 1500 V DC: 0
Contact system	MULTILAM
Type of termination	Crimping
Contact material	Copper, tin plated
Insulation material	PC/PA
Locking system (UL)	Locking type
Flame class	UL94-V0
Ammonia resistance (acc. to DLG)	1500 h, 70 °C / 70% RH, 750 ppm
Salt mist spray test, degree of severity 6	IEC 60068-2-52
TÜV-Rheinland certified, in accordance with IEC 62852	R60110079
TÜV-Rheinland certified, in accordance with 2Pfg2330	R60087448
UL recognized component, in accordance with UL 6703	E343181
CSA certified, in accordance with UL 6703	250725
CQC certified according CNCA/CTS0002-2012	CQC16024138286

<sup>1)</sup> 2Pfg2330: only approved for locations with restricted access

<sup>2)</sup> for selected configurations; see assembly instructions MA231 for details